

6' TANDEM AXLE SPECIFICATIONS 3500# Axles

	ATW610TA2	ATW612TA2	ATW614TA2
OVERALL LENGTH	14' 4"	16' 4"	18' 4"
" WIDTH	7' 9"	7' 9"	7' 9"
" HEIGHT	7' 7"	7' 7"	7' 7"
INTERIOR LENGTH	11' 11"	13' 11"	15' 11"
" WIDTH	5' 8½"	5' 8½"	5' 8½"
" HEIGHT	6' 1½"	6' 1½"	6' 1½"
REAR DOOR(S)	DOUBLE	DOUBLE	DOUBLE
" " WIDTH	4' 11"	4' 11"	4' 11"
" " HEIGHT	5' 5½"	5' 5½"	5' 5½"
HITCH WEIGHT	240 lbs. *	260 lbs. *	280 lbs. *
" HEIGHT	16"	16"	16"
BALL SIZE	2 5/16"	2 5/16"	2 5/16"
PLATFORM HEIGHT	15"	15"	15"
G.A.W.R.	7000 lbs.	7000 lbs.	7000 lbs.
G.V.W.R.	7000 lbs.	7000 lbs.	7000 lbs.
CURB WEIGHT	1800 lbs. *	1950 lbs. *	2100 lbs. *
PAYLOAD CAPACITY	5200 lbs. *	5050 lbs. *	4900 lbs. *
AXLE (TANDEM)	3500 lbs.	3500 lbs.	3500 lbs.
BRAKES	ELECTRIC	ELECTRIC	ELECTRIC
TIRES	ST205/75R15	ST205/75R15	ST205/75R15
WHEELS	5 BOLT	5 BOLT	5 BOLT
FRAME	4" TUBE	4" TUBE	4" TUBE
FLOOR (24"O/C)	3/4" PLYWOOD	3/4" PLYWOOD	3/4" PLYWOOD
SIDE WALLS (16"O/C)	3/8" PLYWOOD	3/8" PLYWOOD	3/8" PLYWOOD

STANDARD FEATURES

RUBBER TORSION AXLES
 E-Z LUBE HUBS w/GREASE CAPS
 PREMIUM RADIAL TIRES
 WHITE MODULAR WHEELS
 S.STEEL CENTER CAPS
 WELDED SAFETY CHAINS
 CAMLOCK DOOR LATCHES
 TRIPLE WEDGE FRONT END
 040 SMOOTH EXTERIOR ALUMINUM
 ONE PIECE ROLLED ROOF

ALL-WHEEL ELECTRIC BRAKES
 12 VOLT BREAKAWAY SWITCH w/BATTERY
 FORMED REAR STEEL HEADER
 INTERIOR WIRING
 DOUBLE SEALED SIDE AND REAR DOOR(S)
 ALUMINUM FENDERS
 MORE CARGO CAPACITY
 HIGH TENSIL "I" BEAM CROSS MEMBERS
 UNDERCOATED FLOOR & CHASSIS

March, 2008