

8' TANDEM AXLE SPECIFICATIONS 5200# Axles

| | ATW816TA3 | ATW818TA3 | ATW820TA3 | ATW822TA3 | ATW824TA3 |
|---------------------|--------------|--------------|--------------|--------------|--------------|
| OVERALL LENGTH | 21' 2" | 23' 2" | 25' 2" | 27' 2" | 29' 2" |
| " WIDTH | 8' 5" | 8' 5" | 8' 5" | 8' 5" | 8' 5" |
| " HEIGHT | 8' 5" | 8' 5" | 8' 5" | 8' 5" | 8' 5" |
| INTERIOR LENGTH | 18' 2" | 20' 2" | 22' 2" | 24' 2" | 26' 2" |
| " WIDTH | 7' 8½" | 7' 8½" | 7' 8½" | 7' 8½" | 7' 8½" |
| " HEIGHT | 6' 8" | 6' 8" | 6' 8" | 6' 8" | 6' 8" |
| REAR DOOR(S) | DOUBLE | DOUBLE | DOUBLE | DOUBLE | DOUBLE |
| " " WIDTH | 7' 3" | 7' 3" | 7' 3" | 7' 3" | 7' 3" |
| " " HEIGHT | 5' 11" | 5' 11" | 5' 11" | 5' 11" | 5' 11" |
| HITCH WEIGHT | 420 lbs. | 440 lbs. * | 460 lbs. * | 480 lbs. * | 500 lbs. * |
| " HEIGHT | 18" | 18" | 18" | 18" | 18" |
| BALL SIZE | 2 5/16" | 2 5/16" | 2 5/16" | 2 5/16" | 2 5/16" |
| PLATFORM HEIGHT | 19" | 19" | 19" | 19" | 19" |
| G.A.W.R. | 5200 lb. |
| G.V.W.R. | 9990 lbs. |
| CURB WEIGHT | 2780 lbs. | 2980 lbs. * | 3180 lbs. * | 3380 lbs. * | 3580 lbs. |
| PAYLOAD CAPACITY | 7210 lbs. | 7010 lbs. * | 6810 lbs. * | 6610 lbs. * | 6410 lbs. |
| AXLE (TANDEM) | 5200 lb. |
| BRAKES | ELECTRIC | ELECTRIC | ELECTRIC | ELECTRIC | ELECTRIC |
| TIRES | ST225/75R15 | ST225/75R15 | ST225/75R15 | ST225/75R15 | ST225/75R15 |
| WHEELS | 6 BOLT |
| FRAME | 6" TUBE |
| FLOOR (24"O/C) | 3/4" PLYWOOD |
| SIDE WALLS (16"O/C) | 3/8" PLYWOOD |

STANDARD FEATURES

RUBBER TORSION AXLES ALL-WHEEL ELECTRIC BRAKES
 INTERIOR WIRING 12 VOLT BREAKAWAY SWITCH w/BATTERY
 PREMIUM RADIAL TIRES FORMED REAR STEEL HEADER
 WHITE MODULAR WHEELS E-Z LUBE HUBS w/GREASE CAPS
 S.STEEL CENTER CAPS DOUBLE SEALED SIDE AND REAR DOOR(S)
 WELDED SAFETY CHAINS TRIPLE WEDGE FRONT END
 CAMLOCK DOOR LATCHES MORE CARGO CAPACITY
 ALUMINUM FENDERS HIGH TENSIL "I" BEAM CROSS MEMBERS
 .040 EXTERIOR ALUMINUM UNDERCOATED FLOOR & CHASSIS
 ONE PIECE ROLLED ROOF

March, 2010